



CAPACITY

Retracted 24,000 lbs.
Extended 8,000 lbs.

REAR SPADES

Hydraulic rear spades with multi-position, ground compacting foot design

EH CONTROLS

Fully proportional Electro-Hydraulic controls

Some optional features shown

ENGINEERED FOR STRENGTH AND DURABILITY

The MPL-60 is a 12 ton Integrated Medium Duty wrecker with a 6,000 lb. rated underlift and a modern, modular aluminum body that is maximized for available storage and deck space.

BECAUSE THE WORK DEMANDS IT.

Want a truck that works as hard as you do?

Visit our website at Jerrdan.com to find your nearest distributor.

SPECIFICATIONS

RECOVERY BOOM: 2-STAGE

Retracted Capacity @ 30°	24,000 lbs.
Extended Capacity @ 30°	8,000 lbs.
Maximum Hook Height	121 in.
Maximum Boom Angle	32°

REACH PAST TAILBOARD

Reach Past Tailboard - Extended @ 0°	84 in.
Reach Past Tailboard - Extended @30°	60 in.

UNDERLIFT BOOM

Retracted Rating L-Arms/Forks	5,000 lbs. / 6,000 lbs.
Retracted Reach L-Arms/Forks	59 in. / 51 in.
Extended Rating L-Arms/Forks	5,000 lbs. / 6,000 lbs.
Extended Reach L-Arms/Forks	87 in. / 78 in.
Positive Tilt	20°
Negative Tilt	20°
Tow Capacity	12,000 lbs.

WINCH

Winch Capacity	10,000 lbs. / 12,000 lbs.
Winch Options	Dual
Wire Rope (EIPS Galvanized)	7/16 in. x 101 ft. (w/Swivel Hook, for 10K Winch) 7/16 in. x 150 ft. (w/Swivel Hook, for 12K Winch)

CHASSIS

Minimum GVW Rating	18,000 lbs.
Minimum Cab-to-Axle, CA	84 in.

MEDIUM DUTY WRECKER

INTEGRATED MPL-60

FEATURES	STANDARD	OPTIONAL
CONTROLS		
Dual Side EH Controls	•	
Wired Underlift Remote Control		•
Wireless Underlift Remote Control*		•
Wireless Full-Function Remote Control*		•
BODY		
No-Lube™ Technology	•	
Greaseable Joints w/ Grease Fittings		•
Lighted Toolboxes	•	
Polished Stainless Rails		•
Aluminum Deck Dress Up Kits*		•
24 in. Aluminum Tunnel Box	•	
Additional 24 in. Aluminum Tunnel Box		•
LIGHTING & ELECTRICAL		
DOT Lighting	•	
Backup Alarm	•	
Fold Down Light Bar Mount		•
In-Cab Switch Panel		•
LED Lower Hook-Up Lights	•	
LED Work Lights Upper - Pylon Mounted		•
Backup Camera Kit		•
Steel Tubular Light Pylon	•	
7-Way RV/4-Way Flat Trailer Connection	•	
Aux Air & Gladhands		•
BOOM & WINCHES		
12T Boom w/Dual Lift Cylinders	•	
Underlift Level Stop Assist System	•	
Winch Rope Tensioner Plate	•	
Remote Freespool Handles	•	
Dual 10,000 lb. Worm Gear Winch	•	
Dual 12,000 lb. Worm Gear Winch		•
Spade Leg and Wrecker Boom D-Rings (3 Total)	•	
Tailboard D-rings		•

*Available through parts only

FEATURES	STANDARD	OPTIONAL
TOWING ACCESSORIES		
L-Arm Storage Brackets w/ Manual Grids	•	
Wheel Lift Tie-Down Straps	•	
Fifth Wheel Plate*		•
Tow Sling & Mounting Brackets		•
Gooseneck Trailer*		•
Hydraulic Tilt Lockout Valve	•	
Self-Loading Aluminum Dollies*		•
Trailer Ball Attachments (available in sizes: 1-7/8 in., 2 in., 2-5/16 in.)*		•

*Available through parts only